

# **lamber**<sup>®</sup> **L25EKS1PH**



This high-temperature pass-through commercial dishwasher is designed for professional kitchens and high-volume food service operations. Combining advanced washing technology, durable stainless steel construction, and simplified maintenance, it delivers powerful cleaning performance and long lasting reliability.

## FEATURES

- Soft-start system protects delicate items and extends component lifespan.
- Safety hood system with automatic cycle start upon closure for seamless and secure operation.
- Built-in detergent and rinse aid pumps ensure precise chemical dosing.
- Thermocontrol system maintains consistent sanitizing rinse temperatures and energy efficiency.



PARTS AND  
LABOR





1-888-956-6866  
customerservice@eurodib.com

[eurodib.com](http://eurodib.com)

## SPECIFICATIONS

Electric pump: 1100 W

Wash tank elements: 3000 W

Rinse tank elements: 6000 W

Total rating: 7100 W

Max. current intensity: 33 A

Wash cycles: 2 - 3 - 4 - 15 min.

Tank capacity: 8.9 Gal (34 L)

Boiler capacity: 2.1 Gal (8 L)

Cycle water consumption:  
0.6 Gal (2 L)

Basket size: 19.6" x 19.6" (50 x 50 cm)

Plates clearance: 16.3" (41 cm)

Inlet water connection:  
131 ÷ 140 °F (55 ÷ 60 °C)

Inlet water pressure: 20 ± 5 psi

Water hardness: 7,2 ÷ 12,5 °F

Rinsing water temperature:  
180 ÷ 195 °F (82 ÷ 90 °C)

Water inlet: ¾" G

Water outlet: 1 ¼"

Noise level: 59,5 dB (A)

Dimensions:

Length: 26.3" (66 cm)

Width: 30.1" (76 cm)

Height: 57" (144 cm)

Connection:



(208/240 V)

Net weight: 308 lb (140 kg)

Shipping dimensions:

Length: 31.5" (80 cm)

Width: 36.6" (92 cm)

Height: 63.3" (160 cm)

Gross weight: 357 lb (162 kg)

## Included accessories

- 1 flat basket, 2 dish baskets and 2 cutlery inserts



2026.05